

## **Portable Gas Generators**

Extremely durable and dependable, every model features simple operation and ease of service. Users and commercial rental centers alike can trust the quality of these generators to give many years of reliable performance.

- 100% copper windings
- Kohler<sup>®</sup> Command PRO<sup>®</sup> OHV engines
- AVR (automatic voltage regulator)
- Large capacity fuel tank with fuel gauge
- GFCI receptacles
- Hour meter
- Wheel kit with flat free tires and folding handles
- 3-year warranty



## **Specifications**

Model	WGC3800	WGC5300	WGC7500E
Emissions Compliancy	EPA, CARB	EPA, CARB	EPA, CARB
Туре	Brush Type	Brush Type	Brush Type
Voltage Regulation	AVR	AVR	AVR
Frequency/Phase	60 Hz/Single	60 Hz/Single	60 Hz/Single
Voltage	120/240	120/240	120/240
Max Output	3800 Watt	5300 Watt	7500 Watt
Max Amps	31.7/15.8	44.2/22.1	62.5/31.2
Rated Output	3500 Watt	4800 Watt	7000 Watt
Rated Amps	29.2/14.6	40/20	58.3/29.2
Sound Level @ 23ft (7m)	72 dBA	72 dBA	76 dBA
Current Protection	Dual Pole Magnetic Circuit Breaker & GFCI	Dual Pole Magnetic Circuit Breaker & GFCI	Dual Pole Magnetic & Thermal Circuit Breaker & GFCI
OHV Engine	Kohler CH270-3056	Kohler CH395-3056	Kohler CH440-3129
Low Oil System	Low Oil Shutdown	Low Oil Shutdown	Low Oil Shutdown
Fuel Tank Capacity	4 gal. (15L)	8 gal. (30L)	8 gal. (30L)
Hours at Rated Load	5.9	8.6	5.9
Hours at 50% Rated Load	11.8	17.4	11.8
Starting System	Recoil	Recoil	Electric with Recoil Backup
Battery Included - Battery Replacement or equal	N/A	N/A	Sealed 12 V 18 Ahr Interstate BSL1116
Dimensions with wheel kit, handles folded down (L $\times$ W $\times$ H)	$27 \times 25 \times 26$ in. ( $67 \times 64 \times 66$ cm)	$30 \times 29 \times 29$ in. (76 × 74 × 74cm)	$30 \times 29 \times 29$ in. (76 $\times$ 74 $\times$ 74cm)
Dimensions without wheel kit $(L \times W \times H)$	$25 \times 17 \times 20$ " (64 × 43 × 51cm)	28 × 21 × 24" (71 × 53 × 61cm)	$28 \times 21 \times 24''$ (71 × 53 × 61cm)
Dry Weight (includes wheel kit)	137 lbs. (62kg)	215 lbs. (98kg)	227 lbs. (103kg)
GFCI 120V 20 Amp. Duplex	2	2	2
120V 30 Amp. Twist Lock	N/A	1	1
120/240V 30 Amp. Twist Lock	1	1	1
Hour Meter	Yes	Yes	Yes
Wheel Kit	Yes	Yes	Yes

Due to Wanco's commitment to continuous improvement of our products, all information is subject to change without notice. Wanco and the Wanco logo are registered trademarks of Wanco Inc. All other trademarks are property of their respective owners.

WANCO INC. 5870 Tennyson Street Arvada, Colorado 80003 800-972-0755 303-427-5700 303-427-5725 fax www.wanco.com

